

# **SEISMIC PROPERTIES OF SHALLOW-WATER SEDIMENTS: A COMPONENT OF THE STRATAFORM PROGRAM**

LeRoy M. Dorman  
Marine Physical Laboratory and Geological Research Division  
Scripps Institution of Oceanography, 0215  
University of California, San Diego  
La Jolla CA, 92093-0215  
Email: ldorman@ucsd.edu Voice: (619) 534-2406 Fax: (619) 534-6849  
N00014-96-1-0508

## **LONG-TERM GOAL**

The long-term scientific objective is to enhance our knowledge of the ocean environment (in this case the littoral seafloor) and the processes which govern it.

## **SCIENTIFIC OBJECTIVES**

The project objectives are to aid in the understanding of the formation of stratigraphy on margins. This particular part of this effort is focussed on the measurement of seafloor shear velocities off Humboldt Bay, the west coast STRATAFORM site. Shear wave velocity is the most variable of the seismic parameters and has the most potential as a "remote-sensing" diagnostic tool.

## **APPROACH**

The approach used is to fire a few small (1/2 lb) seafloor shots and measure the dispersion of seafloor interface (Scholte waves) and then to invert the dispersed waveform to obtain seafloor structure.

## **WORK COMPLETED**

This grant supported field work to collect Scholte-wave data in the Strataform study area. We report here on seafloor seismic observations made during August of 1996 off Humboldt Bay, Northern California, in the 50m-200m water depth range. Scholte interface waves generated by four half-pound seafloor explosions were observed by ocean-bottom seismometers and hydrophones.

## **RESULTS**

The data giving information about sediment shear velocities are in the 2-7 Hz frequency range. Initial examination of the group velocities reveals the following:

1. At 200 m water depth, on a bottom reported to be gassy mud, the group velocity centroid is about 100 m/s and is strongly dispersed. See panel (a) in accompanying figure.
2. At 50m water depth, on a "sandy" bottom, the group velocity is 200 m/s and the dispersion is slight. See panel (b) in accompanying figure.

These observations are consistent with rapid deposition in the shallow region and slower deposition (with accompanying compaction) in the muddy area.

The values in the sandy area are comparable to shear velocities observed off Southern California. The group velocities observed in the muddy area are slower than in the sandy area, but are several times faster than the velocities found in pelagic muds.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>30 SEP 1997</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-1997 to 00-00-1997</b>	
4. TITLE AND SUBTITLE <b>Seismic Properties of Shallow-water Sediments: A Component of the Strataform Program</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>University of California, San Diego, Scripps Institution of Oceanography, Marine Physical Laboratory and Geological Research Division, La Jolla, CA, 92093</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>3</b>	19a. NAME OF RESPONSIBLE PERSON
a REPORT <b>unclassified</b>	b ABSTRACT <b>unclassified</b>	c THIS PAGE <b>unclassified</b>			

The noise levels are fairly high because of the shallow depth and bumpy weather. Some impulsive noises recorded on the seismic sensors are correlated with lower-frequency pressure waves recorded on hydrophones.

Three OBSs were equipped with geochemical fluxmeters (Brown and others 1996) and these generally showed fluid outflow.

### **IMPACT/APPLICATION**

Shear velocity has some potential to be an indicator of shear strength, which is probably related to resistance to mechanical slumping.

### **TRANSITIONS**

The shear velocity of clathrate-containing sediment should be higher than that of non-frozen sediments. Presence of bubbles should lower the compressional velocity markedly, but not change the shear velocity nearly as much.


### **RELATED PROJECTS**

Some similar work measuring Scholte wave velocities using interface waves has been carried out off Southern California. See WWW reference below.


### **REFERENCES**

There is related shallow-water work at <http://www-mpl/obs/reports/abm>.

- Dorman, L. M., Sauter, A. W., Bradley, C. R., Wiggins, S., Kanjorski, N., Avera, W., and Bibee, L. D., Seafloor Shear Velocities off Humboldt Bay, EOS, Transactions AGU, 97, 1996.
- Brown, K. M., Sauter, A. W., and Dorman, L. M., A new fluid and geochemical flux meter for surface measurements in convergent margin and ridge flank environments, Geophys. Res. Letts., in revision, 14, 1996.



a) from "gassy sediment" site



b) from "sandy" site